

# Excavator Komatsu PC300LC-6/ PC300LC-7/ PC350-6/PC350LC-7slewing Ring, Swing Circle

Excavator Komatsu PC300LC-6/ PC300LC-7/  
PC350-6/PC350LC-7slewing Ring, Swing Circle Industries and  
Applications ? We sell discount online as well as Mounted  
Bearing Engineering Group cheap machinery parts.

Engineering Group	Mounted Bearing
Shaft Size	60 mm
Shaft Size Type	Metric
Full Timken Part Number	QASN13A060SB
Locking Style	Single Concentric
Weight	35 lb
Housing Style	Two-Bolt Pillow Block
UPC Code	0883450353441
Dimension A	3.15 in
Dimension B	6.18 in
Dimension C	3.81 in
Dimension D Max	9.25 in
Dimension D Min	7.72 in
Dimension F	10.83 in
Dimension G	2.910 in
Dimension H	1.38 in
Dimension J (Bolt Size)	0.625 in
Dimension KA	1.22 in

Dimension L	3.62 in
Dimension M	2.17 in
Dimension RA	0.24 in
Dimension SA	3.39 in
C0 – Static Load	48600 lb
C – Dynamic Load (Basic)	46400 lb
e – Geometry Factor	0.24
Y1 – Geometry Factor	2.79
Y2 – Geometry Factor	4.15
Oil Lubrication – M/N Seal	1800 rpm
Oil Lubrication – T Seal	3200 rpm
Oil Lubrication – B/C/O Seal	1500 rpm
Grease Lubrication – M/N Seal	1800 rpm
Grease Lubrication – T Seal	2800 rpm
Grease Lubrication – B/C/O Seal	1500 rpm
Float	0.083 in
Shaft Tolerance	0.0015 in
Eng Internal Radial Clearance – Min	0.0016
Eng Internal Radial Clearance – Max	0.0026
Pre Install Clearance Min	0.0016 in
Pre Install Clearance Max	0.0026 in