

Excavator Komatsu PC600-7/ PC600LC-6 Slewing Ring, Swing Circle, Slewing Bearing

LET OUR Excavator Komatsu PC600-7/ PC600LC-6 Slewing Ring, Swing Circle, Slewing Bearing Imperial Shaft Size Type EXPERTS GET YOU THE PARTS YOU NEED. Mounted Bearing Engineering Group

Engineering Group	Mounted Bearing
Shaft Size	2-1/2 in
Shaft Size Type	Imperial
Full Timken Part Number	QMFL13J208SB
Locking Style	Eccentric
Weight	17.0 lb
Housing Style	Four-Bolt Square Flange
UPC Code	0883450070522
Dimension BC	6.75 in
Dimension C	3.62 in
Dimension D	5.750 in
Dimension E	4.77 in
Dimension F	6.19 in
Dimension H	1.00 in
Dimension J (Bolt Size)	0.625 in
Dimension K	1.24 in
Dimension L Exp	3.57 in
Dimension L Fix	3.47 in
Dimension M	2.13 in
Dimension N	2.860 in

Dimension R	0.12 in
Dimension S	2.32 in
C0 – Static Load	48600 lb
C – Dynamic Load (Basic)	46400 lb
e – Geometry Factor	0.25
Y1 – Geometry Factor	2.69
Y2 – Geometry Factor	4.00
Oil Lubrication – M/N Seal	1800 rpm
Oil Lubrication – T Seal	3200 rpm
Oil Lubrication – B/C/O Seal	1500 rpm
Grease Lubrication – M/N Seal	1800 rpm
Grease Lubrication – T Seal	2800 rpm
Grease Lubrication – B/C/O Seal	1500 rpm
Float	0.083 in
Shaft Tolerance	0.0015 in
Eng Internal Radial Clearance – Min	0.0016
Eng Internal Radial Clearance – Max	0.0026
Pre Install Clearance Min	0.0016 in
Pre Install Clearance Max	0.0026 in