

# Excavator Sumitomo Sh240-5 Slewing Bearing, Slewing Ring, Swing Circle

We Provide Extensive Excavator Sumitomo Sh240-5 Slewing Bearing, Slewing Ring, Swing Circle Selection And Competitive 61.913 mm da Wholesale Pricing.

da	61.913 mm
Da	160 mm
Ca	64.795 mm
A1	98.425 mm
A2	223.838 mm
ba	35.719 mm
H	192.088 mm
H1	101.6 mm
H2	41.275 mm
J min.	263.525 mm
J max.	295.275 mm
J1	53.975 mm
L	349.25 mm
N1	19.05 mm
R1	60.325 mm
R2	27.94 mm
RG	3/8 NPT
PG	1/8 NPT
h	42.862 mm
Housing	FSAF 615

Bearing	1315 K
Adapter sleeve assembly	SNW 15×2.7/16
Stabilizing ring	2 x SR-1615
Taconite seal	TER 37
End plug (suffix Y)	EPR 7
Max. speed for Taconite seal	1250 r/min
P60°	101 kN
P90°	60.9 kN
P120°	38.3 kN
P150°	34.7 kN
P180°	42.3 kN
Pa	8.27 kN
Mass pillow block	21.5 kg
Cap bolt	2 x 5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.625 in
Initial grease fill	286.33 g