

Excavator Takeuchi 1140 Swing Circle, Slewing Ring, Slewing Bearing

Excavator Takeuchi 1140 Swing Circle, Slewing Ring, Slewing Bearing SEARCH – Whether it's agriculture or construction equipment your working on, Has the you need. 90.488×161.925×47.625 Size (mm)

Size (mm)	90.488×161.925×47.625
Bore Diameter (mm)	90,488
Outer Diameter (mm)	161,925
Width (mm)	47,625
d	90,488 mm
D	161,925 mm
T	47,625 mm
B	48,26 mm
C	38,1 mm
ra1 max.	3,3 mm
a	35,6 mm
r min.	3,5 mm
r1 min.	3,3 mm
Da	144 mm
db	101 mm
ra max.	3,5 mm
da	107 mm
Db	150 mm
Weight	3,99 Kg
Basic dynamic load rating (C)	274 kN

Basic static load rating (C0)	390 kN
(Grease) Lubrication Speed	2200 r/min
(Oil) Lubrication Speed	3000 r/min
Calculation factor (e)	0,34
Calculation factor (Y0)	0,97
LangID	1
ALP23	20
outer r	3.3
ALP22	37
D_	161.925
ALP21	25
SHOG_yobi	760R/752R
RAr	330.864
inner r	3.5
GRS rpm	2200
D_b	150
D_a	144
DE_	138.839
SLR	34
Prod_Type3	TRBSR_ID_A
BETA_	1
ALPHA_	12.811
SDM_	122.225
DA1	18.283
DA2	16.411
hidYobi	760/752
Y1	1.8
B_	48.26
Oil rpm	3000

hidTable	ecat_NSTPRI
Y0	0.97
inner ra	3.5
outer rb	3.3
C0	390
CUP	1.61
e	0.34
DA_	17.351
BET21	3
BET22	10
BET23	0
Z_	19
C_	38.1
yobi	760/752
KBRG	3161
CONE	2.38
DI_	105.124