

EXT204+WB SNR C 12.8 kN

Bearing units

| | |
|---|-----------|
| A1 | 12 mm |
| B | 34 mm |
| A5 | 17 mm |
| d1 | 32.4 mm |
| G | M6x1 |
| H1 | 76 mm |
| H2 | 51 mm |
| L1 | 61 mm |
| L3 | 51 mm |
| N1 | 16 mm |
| N2 | 32 mm |
| s1 | 30.5 mm |
| S | 17 mm |
| C | 12.8 kN |
| C0 | 6.65 kN |
| T min. | -20 °C |
| T max. | 100 °C |
| Recommended tightening torque for set screw | 5.5 Nm |
| Designation of housing | T204- |
| Designation of bearing | EX204G2 |
| Bearing number | EXT204+WB |
| Brand | SNR |
| Bore Diameter (mm) | 20 |
| d | 20 mm |
| A4 | 367 mm |

| | |
|-------------------------------|---------|
| P | 150 mm |
| e | 29 mm |
| L2 | 83 mm |
| s | 17 mm |
| SW | 11 mm |
| A | 50 mm |
| B1 | 43.5 mm |
| D2 | 33.3 mm |
| H | 199 mm |
| J | 154 mm |
| L | 317 mm |
| M | 117 mm |
| M1 | 19 mm |
| N | 12 mm |
| T | 6 mm |
| A2 | 55.5 mm |
| Weight | 5.2 Kg |
| Basic dynamic load rating (C) | 12.8 kN |