

# External Gear Slewing Rings for Excavators

Welcome to the External Gear Slewing Rings for Excavators 0.0 Inventory N/A Minimum Buy Quantity online seller. REXNORD Manufacturer Name

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REXNORD   |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 19.52   |
| EAN                       | 0662327956691   |
| Product Group             | M06288  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Concentric Collar   |
| Housing Style             | 4 Bolt Pillow Block   |
| Rolling Element           | Spherical Roller Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 3/4 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | B22455HL  |
| Seals                     | Floating Labyrinth  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Double Row   Single Collar   Extended Inner Race   With Set Screw |

|                               |   |
|-------------------------------|---|
| Long Description              | 4 Bolt Pillow Block; 3-7/16" Bore; 3-3/4" Base to Center Height; Concentric Collar Mount; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | PEB22455FHK54   |
| Manufacturer Internal Number  | 5895669   |
| Weight / LBS                  | 43  |
| D                             | 4.375 Inch   111.13 Millimeter  |
| Nominal Bolt Center to Center | 10 Inch   254 Millimeter  |
| d                             | 3.438 Inch   87.325 Millimeter  |
| B                             | 3.75 Inch   95.25 Millimeter  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |
| Actual Bolt Center to Center  | 10 Inch   254Millimeter   |