

FAG 22228-E1-K + AHX3128 spherical roller bearings

Online 40 Outer Diameter (mm) FAG 22228-E1-K + AHX3128 spherical roller bearings Expert.More Choices. FAG 22228-E1-K + AHX3128 spherical roller bearings in Stock & Ready to Ship 80x40x18 Size (mm) Now!

Size (mm)	80x40x18
Bore Diameter (mm)	80
Outer Diameter (mm)	40
Width (mm)	18
d	40 mm
D	80 mm
B	18 mm
d1	52.6 mm
D2	69.8 mm
r1,2 – min.	1.1 mm
da – min.	47 mm
da – max.	52.5 mm
Da – max.	73 mm
ra – max.	1 mm
Basic dynamic load rating – C	32.5 kN
Basic static load rating – C0	19 kN
Limiting speed	150 r/min
Limiting temperature – T	350 °C
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A

Weight / Kilogram	0.382
EAN	7316571439532
Product Group	B00308
Enclosure	2 Metal Shields
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Coronet Cage
Cage Material	Graphite
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	40MM Bore; 80MM Outside Diameter; 18MM Outer Race Width; 2 Metal Shields; Ball Bearing; ABEC 1 ISO
Other Features	Deep Groove Extreme Temperature Variant
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6208-2Z/VA228
Weight / LBS	0.807
Inner Race Width	0 Inch 0 Millimeter
Outside Diameter	3.15 Inch 80 Millimeter
Bore	1.575 Inch 40 Millimeter
Outer Race Width	0.709 Inch 18 Millimeter
bore diameter:	40 mm
precision rating:	ABEC 3 (ISO Class 6)

outside diameter:	80 mm
finish/coating:	Uncoated
overall width:	18 mm
cage material:	Graphite
bore type:	Round
outer ring width:	18 mm
closure type:	Double Shielded
fillet radius:	1.1 mm
row type & fill slot:	Single Row Non-Fill Slot
maximum rpm:	150 RPM
internal clearance:	C0
series:	62
operating temperature range:	-240 to +660 °F
resistance features:	Corrosion Resistant, Extreme Temperature
static load capacity:	19 kN
d1 ≈	52.6 mm
D2 ≈	69.8 mm
r1,2 min.	1.1 mm
da min.	47 mm
da max.	52.5 mm
Da max.	73 mm
ra max.	1 mm
Basic dynamic load rating C	32.5 kN
Basic static load rating C0	19 kN
Limiting temperature T max.	350 °C
Mass bearing	0.38 kg