

FAG 22268-B-K-MB spherical roller bearings

100% Authentic. FAG 22268-B-K-MB spherical roller bearings N/A Minimum Buy Quantity Highest 0.0 Inventory Quality. Certified Supplier.

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	52 lb
EAN	0053893540627
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	3/4 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Metric
Long Description	4 Bolt Square Flange Block; 80MM Bore; 251.7MM Bolt Circle; 177.8MM Bolt Spacing; 1 Piece Solid; Con

Other Features	Double Row Wide Inner Race With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	E-4BF-TRB-80MM
Weight / LBS	52
D	5 Inch 127 Millimeter
Bolt Spacing	7 Inch 177.8 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter
d	3.15 Inch 80 Millimeter
Nominal Bolt Circle Diameter Round	9.9 Inch 251.7 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Shaft Size	3.15 in
Shaft Size Type	Metric
UPC Code	053893540627
Dimension B	5 in
Dimension L	9-1/4 in
Dimension A	4-1/2 in
Dimension J	7 in
Dimension A2	1/4 in
Bolt Diameter	3/4 in
Dimension A1	1-7/8 in
Dimension D 1	7-1/4 in
Dimension d1	5-17/32 in
e	0.50
X (if $F_a/F_r \leq e$)	0.87

Y (if $F_a/F_r \leq e$)	1.71
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.07
K Factor	1.19
C90 Dynamic Load Rating ²	19600 lb
C0 Static Load Rating	108600 lb
Fa-max Maximum Permissible Thrust Load ³	5181 lb
Fr-max Maximum Allowable Slip Fit Radial Load ⁴	16000 lb
Max. Speed ⁵	1640 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to