

FAG 22336-E1-K-JPA-T41A + AH2336G spherical roller bearings

FAG 22336-E1-K-JPA-T41A + AH2336G spherical roller bearings Warehouse 90x40x23 Size (mm) offers car parts 90 Bore Diameter (mm) and car accessories. We sell discount online as well as cheap machinery parts.

Size (mm)	90x40x23
Bore Diameter (mm)	90
Outer Diameter (mm)	40
Width (mm)	23
d	40 mm
D	90 mm
B	23 mm
d1	59.7 mm
d2	49.55 mm
D1	71.6 mm
a	39 mm
r1,2 – min.	1.5 mm
r3,4 – min.	1 mm
da – min.	49 mm
Da – max.	81 mm
Db – max.	84.4 mm
ra – max.	1.5 mm
rb – max.	1 mm
Basic dynamic load rating – C	50 kN
Basic static load rating – C0	32.5 kN

Fatigue load limit – Pu	1.4 kN
Reference speed	10000 r/min
Limiting speed	10000 r/min
Calculation factor – kr	0.1
Calculation factor – ka	1.6
Calculation factor – e	1.14
Calculation factor – X	0.35
Calculation factor – Y0	0.26
Calculation factor – Y1	0.55
Calculation factor – Y2	0.57
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.61
EAN	7316577150554
Product Group	B00308
Enclosure	Open
Flush Ground	Yes
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Preload	Light
Mounting Arrangement	Universal

Inch – Metric	Metric
Long Description	40MM Bore; 90MM Outside Diameter; 23MM Width; Open; Yes Flush Ground; Ball Bearing; Single Row of Ba
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer Item Number	7308 BEGAP
Weight / LBS	1.347
Bore	1.575 Inch 40 Millimeter
Outside Diameter	3.543 Inch 90 Millimeter
Width	0.906 Inch 23 Millimeter
bore diameter:	40 mm
radial static load capacity:	32.5 kN
outside diameter:	90 mm
cage material:	Nylon
overall width:	23 mm
outer ring width:	23 mm
contact angle:	40 °
maximum rpm:	10000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	1.5 mm
radial dynamic load capacity:	50 kN
series:	73

d1 ≈	59.7 mm
d2 ≈	49.55 mm
D1 ≈	71.6 mm
r1,2 min.	1.5 mm
r3,4 min.	1 mm
da min.	49 mm
Da max.	81 mm
Db max.	84.4 mm
ra max.	1.5 mm
rb max.	1 mm
Basic dynamic load rating C	50 kN
Basic static load rating C0	32.5 kN
Fatigue load limit Pu	1.37 kN
Calculation factor A	0.0173
Calculation factor kr	0.1
Calculation factor e	1.14
Calculation factor X	0.57
Calculation factor Y0	0.52
Calculation factor Y2	0.93
Calculation factor Y1	0.55
Mass bearing	0.62 kg