

FAG 230/670-B-K-MB spherical roller bearings

How do I place an EMERGENCY order for a FAG 230/670-B-K-MB spherical roller bearings that I 55 Bore Diameter (mm) want to pick up at a our 55x100x26.75 Size (mm) store?

Size (mm)	55x100x26.75
Bore Diameter (mm)	55
Outer Diameter (mm)	100
Width (mm)	26,75
d	55 mm
D	100 mm
T	26,75 mm
B	25 mm
C	21 mm
ra1 max.	1,5 mm
a	22,5 mm
r min.	2 mm
r1 min.	1,5 mm
da min.	65 mm
Da min	87 mm
Da max.	91,5 mm
db max.	63 mm
Db min.	95 mm
ra max.	2 mm
Sa	4 mm
Sb	5,5 mm
Weight	0,876 Kg

Basic dynamic load rating (C)	108 kN
Basic static load rating (C0)	134 kN
(Grease) Lubrication Speed	3 600 r/min
(Oil) Lubrication Speed	4 900 r/min
Calculation factor (e)	0,4
Calculation factor (Y0)	0,81
d1	76 mm
rs min	2 mm
r1s min	1.5 mm
e	0.4
Y2	1.48
Y0	0.81
Mass	0.88 kg
ISO 355 reference	T3DC055
Dynamic load, C	108 kN
Rating life coefficient, A2	1.4
Static load, C0	134 kN
Fatigue limit load, Cu	16.3 kN
Nlim (oil)	4,900 rpm
Nlim (grease)	3,600 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	6.36 Hz
Characteristic outer ring frequency, BPF0	8.09 Hz
Characteristic inner ring frequency, BRFI	10.91 Hz
da max	63 mm
db min	65 mm
Da max	91.5 mm

Db min	95 mm
Ca min	4 mm
Cb min	5.5 mm
ra max	2 mm
r1a max	1.5 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0
EAN	4547359003499
Product Group	B04334