

FAG 23068-K-MB + AH3068G-H spherical roller bearings

YOU'LL 20 mm d FIND AN 35 mm D EXTENSIVE SELECTION OF FAG 23068-K-MB + AH3068G-H spherical roller bearings FOR SALE.

d	20 mm
D	35 mm
B	7 mm
rs min	0.3 mm
Radial clearance class	CN
Mass	0.02 kg
Dynamic load, C	4 kN
Static load, C0	2.47 kN
Fatigue limit load, Cu	0.11 kN
f0	15.5
Nlim (grease)	21,000 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.29 Hz
Characteristic outer ring frequency, BPF0	5.62 Hz
Characteristic inner ring frequency, BPFI	7.38 Hz
da min	22 mm
da max	22.5 mm
Da max	33 mm

ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.026
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	Riveted Cage
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	20MM Bore; 32MM Outside Diameter; 7MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No F
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.042
Inner Race Width	0 Inch 0 Millimeter

Outside Diameter	1.26 Inch 32 Millimeter
Bore	0.787 Inch 20 Millimeter
Outer Race Width	0.276 Inch 7 Millimeter