

FAG 230S.607-MA spherical roller bearings

With over 10170 full-service stores, our 34.5×31.75×13 Size (mm) FAG 230S.607-MA spherical roller bearings 34,5 Bore Diameter (mm) inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your productivity by saving time and your hard-earned dollars.

Size (mm)	34.5×31.75×13
Bore Diameter (mm)	34,5
Outer Diameter (mm)	31,75
Width (mm)	13
d	31.75 mm
A1	34.5 mm
A2	13 mm
J	92 mm
L	118 mm
T	46.4 mm
H	14.3 mm
B	42.9 mm
s1	25.4 mm
Basic dynamic load rating – C	25.5 kN
Basic static load rating – C0	15.3 kN
Limiting speed	170 r/min
Limiting temperature – T	350 °C
Mass bearing unit	1.52 kg
Grub (set) screw – G2 – 5/16-24 UNF	5/1624 UNF

Hexagonal key size for grub screw – H	3.969 mm
Recommended tightening torque for grub screw	6.5 N·m
Inventory	2.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.5
EAN	7316571381213
Product Group	M06110
Number of Mounting Holes	4
Mounting Method	Set Screw
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	YAR 207-104-2FW/VA228
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-1/4" Bore; 5.1" Bolt Circle; 3-5/8" Bolt Spacing; 1 Pie
Other Features	Single Row Standard Duty Wide Inner Race Open End High Temperature Bearing with Graphite H

UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FY 1.1/4 TF/VA228
Weight / LBS	3.3
Cartridge Pilot Diameter	0 Inch 0 Millimeter
Bore	1.25 Inch 31.75 Millimeter
Nominal Bolt Circle Diameter Round	5.1 Inch 130 Millimeter
Cartridge Pilot Depth	0 Inch 0 Millimeter
Length Thru Bore	1.688 Inch 42.87 Millimeter
Bolt Spacing	3.625 Inch 92.08 Millimeter
bore diameter:	1.2500 in
radial dynamic load capacity:	5733 lbf
bolt center-to-center length:	3.6220 in
radial static load capacity:	3440 lbf
overall length/diameter:	4.6457 in
length through bore:	1.6890 in
overall height:	1.8268 in
finish/coating:	Blue Alkyd/Acryl Paint (RAL 5007)
bore type:	Round
bolt size:	0.5630 in
mounting type:	Four-Bolt Flange
maximum rpm:	170 rpm
housing material:	Cast Iron
lubrication type:	Lubrication Fitting

locking device:	Set Screw
series:	FY
expansion type:	Non-Expansion Bearing (Fixed)
manufacturer product page:	Click here
bearing material:	Steel
manufacturer upc number:	7316571381213
N	14.3 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C0	15.3 kN
Limiting temperature T max.	350 °C
Grub (set) screw G2	5/16-24 UNF
Hexagonal key size for grub screw N	3.969 mm
Attachment bolts, recommended metric size G	12 mm
Bearing	YAR 207-104-2FW/VA228