

FAG 239/710-K-MB+H39/710 spherical roller bearings

How do you find 62 mm D the 16 mm B FAG 239/710-K-MB+H39/710 spherical roller bearings specification? Manufacturers Online Free check 30 mm d

d	30 mm
D	62 mm
B	16 mm
a min	3.07 mm
a max	3.28 mm
Ca min	4.67 mm
Ca max	4.98 mm
rs min	1 mm
rNs min	0.5 mm
D3 max	59.61 mm
b min	1.9 mm
b max	2.2 mm
r0 max	0.6 mm
D4 max	67.7 mm
f	1.7 mm
Snap ring reference	R62
Radial clearance class	CN
Mass	0.2 kg
Dynamic load, C	19.5 kN
Static load, C0	11.3 kN
Fatigue limit load, Cu	0.51 kN
f0	13.8

Nlim (grease)	11,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.68 Hz
Characteristic outer ring frequency, BPF0	3.58 Hz
Characteristic inner ring frequency, BRFI	5.42 Hz
da min	35 mm
Da max	57 mm
ra max	1 mm
rNa max	0.5 mm
Db min	68.5 mm