

FAG 23968-MB spherical roller bearings

What 30 mm d are the dimensions of a FAG 23968-MB spherical roller bearings? Manufacturing Service . Get 30 Bore Diameter (mm) Your Free, Instant Quote

Bore Diameter (mm)	30
Outer Diameter (mm)	48
d	30 mm
Fw	30 mm
D	42 mm
D1	47 mm
D2	48 mm
C	30 mm
a	42,7 mm
r min.	0,6 mm
C1	11 mm
da min.	40 mm
ra max.	0,6 mm
C2	9,5 mm
Weight	0,148 Kg
Dynamic load rating radial (C)	22,3 kN
Dynamic load rating axial (C)	20,4 kN
Static load rating radial (C0)	39,5 kN
Static load rating axial (C0)	42 kN
(Grease) Lubrication Speed	4300 r/min
dw	30 mm
rs min	0.6 mm

Dw	2.5 mm
Dw1	6.35 mm
Lw	15.8 mm
Lubrication hole on outer ring	Oui/Yes
Precision class	P0
Mass	0.15 kg
Cr	22.3 kN
Ca	20.4 kN
C0r	39.5 kN
C0a	42 kN
Nlim (grease)	4,300 rpm
Nlim (oil)	6,200 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
da min	40 mm
ras max	0.6 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.146
Product Group	B04144