

FAG 32234-XL-DF-A490-540 tapered roller bearings

YOU'LL FIND AN EXTENSIVE SELECTION 20 mm d 52 mm D OF FAG 32234-XL-DF-A490-540 tapered roller bearings FOR SALE.

d	20 mm
D	52 mm
B	15 mm
rs min	1.1 mm
Radial clearance class	C3
Mass	0.14 kg
Dynamic load, C	15.9 kN
Static load, C0	7.9 kN
Fatigue limit load, Cu	0.36 kN
f0	12.4
Nlim (grease)	14,000 rpm
Min operating temperature, Tmin	-25 °C
Max operating temperature, Tmax	110 °C
Characteristic cage frequency, FTF	0.37 Hz
Characteristic rolling element frequency, BSF	3.52 Hz
Characteristic outer ring frequency, BPF0	2.57 Hz
Characteristic inner ring frequency, BRFI	4.43 Hz
da min	26.5 mm
da max	28.5 mm
Da max	45.5 mm

ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.145
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Non-Contact Seal
Internal Clearance	C3-Loose
Inch – Metric	Metric
Long Description	20MM Bore; 52MM Outside Diameter; 15MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Non-Friction Nitrile Rubber Seal Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Weight / LBS	0.32
Bore	0.787 Inch 20 Millimeter

Outer Race Width	0.591 Inch 15 Millimeter
Outside Diameter	2.047 Inch 52 Millimeter
Inner Race Width	0 Inch 0 Millimeter