

FAG 32968-N11CA-VA240-300 tapered roller bearings

How do you find the FAG 32968-N11CA-VA240-300 tapered roller bearings specification? Manufacturers Online Free 150x90x45 Size (mm) check

Size (mm)	150x90x45
Bore Diameter (mm)	150
Outer Diameter (mm)	90
Width (mm)	45
d	90 mm
D	150 mm
T	45 mm
d1	120.38 mm
B	45 mm
C	35 mm
r1,2 – min.	2.5 mm
r3,4 – min.	2 mm
a	34.671 mm
da – max.	100 mm
db – min.	100 mm
Da – min.	130 mm
Da – max.	140 mm
Db – min.	144 mm
Ca – min.	7 mm
Cb – min.	10 mm
ra – max.	2.5 mm
rb – max.	2 mm

Basic dynamic load rating – C	251 kN
Basic static load rating – C0	390 kN
Fatigue load limit – Pu	43 kN
Reference speed	3000 r/min
Limiting speed	4300 r/min
Calculation factor – e	0.4
Calculation factor – Y	1.5
Calculation factor – Y0	0.8
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	3.165
EAN	7316577006394
Product Group	B04334
bore diameter:	90 mm
dynamic load capacity:	251 kN
cup width:	35 mm
static load capacity:	390 kN
assembly type:	Cone & Cup
finish/coating:	Uncoated
outside diameter:	150 mm
maximum rpm:	4300 RPM
cone width:	45 mm
series:	331
closure type:	Open
flange type:	Non-Flanged Cup
operating temperature range:	Maximum of +250 °F