

FAG 572428 tapered roller bearings

are a 16 Bore Diameter (mm) few brands 16x18x15 Size (mm) 18 Outer Diameter (mm) you will find in our inventory. Find FAG 572428 tapered roller bearings to see what's in stock!

| | |
|--|-----------------------|
| Size (mm) | 16x18x15 |
| Bore Diameter (mm) | 16 |
| Outer Diameter (mm) | 18 |
| Width (mm) | 15 |
| d | 16 mm |
| D | 18 mm |
| B | 15 mm |
| c1 min | 0,1 mm |
| c2 min | 0,2 mm |
| M | 3 mm |
| Weight | 0,0045 Kg |
| Basic dynamic load rating (C) | 29 kN |
| c1 min. | 0.1 mm |
| c1 max. | 0.6 mm |
| c2 min. | 0.2 mm |
| c2 max. | 1 mm |
| $\alpha \pm 8$ | 20 ° |
| Tolerance shaft | h8 |
| Tolerance housing | H7 |
| Basic dynamic load rating – radial direction C | 29 kN |
| Basic static load rating – radial direction C0 | 60 kN |
| Specific dynamic load factor K | 120 N/mm ² |

| | |
|---|-----------------------|
| Specific static load factor K_0 | 250 N/mm ² |
| Factor depending on material and bearing type K_M | 1900 |
| Permissible sliding velocity v min. | 0 m/s |
| Permissible sliding velocity v max. | 2.5 m/s |
| Coefficient of friction μ min. | 0.02 |
| Coefficient of friction μ max. | 0.2 |
| Mass bushing | 0.0045 kg |