## FAG B71916-C-T-P4S angular contact ball bearings

FAG B71916-C-T-P4S angular contact ball bearings, Units and Housings CAD models , 2-3/4 in Shaft Size Mounted Bearing Engineering Group Manufacturing Service . Get Your Free.

| Engineering Group       | Mounted Bearing         |
|-------------------------|-------------------------|
| Shaft Size              | 2-3/4 in                |
| Shaft Size Type         | Imperial                |
| Full Timken Part Number | QVF16V212SB             |
| Locking Style           | Single V-Lock           |
| Weight                  | 23 lb                   |
| Housing Style           | Four-Bolt Square Flange |
| UPC Code                | 0883450039994           |
| Dimension BC            | 8.48 in                 |
| Dimension C             | 4.19 in                 |
| Dimension D             | 6.650 in                |
| Dimension E             | 6.000 in                |
| Dimension F             | 7.44 in                 |
| Dimension H             | 1.06 in                 |
| Dimension J (Bolt Size) | 0.75 in                 |
| Dimension L             | 3.45 in                 |
| Dimension L Exp         | 3.53 in                 |
| Dimension L Fix         | 3.45 in                 |
| Dimension N             | 2.980 in                |
| Dimension RV            | 0.16 in                 |
| Dimension SV            | 3.29 in                 |
| CO — Static Load        | 62500 lb                |

| C — Dynamic Load (Basic)            | 57200 lb  |
|-------------------------------------|-----------|
| e — Geometry Factor                 | 0.22      |
| Y1 - Geometry Factor                | 3.01      |
| Y2 - Geometry Factor                | 4.48      |
| Oil Lubrication — M/N Seal          | 1500 rpm  |
| Oil Lubrication — T Seal            | 2650 rpm  |
| Oil Lubrication — B/C/O Seal        | 1200 rpm  |
| Grease Lubrication — M/N Seal       | 1500 rpm  |
| Grease Lubrication — T Seal         | 2200 rpm  |
| Grease Lubrication — B/C/O Seal     | 1150 rpm  |
| Float                               | 0.083 in  |
| Shaft Tolerance                     | 0.0020 in |
| Eng Internal Radial Clearance — Min | 0.0037    |
| Eng Internal Radial Clearance — Max | 0.0047    |
| Pre Install Clearance Min           | 0.0037 in |
| Pre Install Clearance Max           | 0.0047 in |