

FAG BSB040072-T thrust ball bearings

Find the discount FAG BSB040072-T thrust ball bearings online you need 32 Outer Diameter (mm) . 15x32x9 Size (mm) We offer ... If you check out our large selection of FAG BSB040072-T thrust ball bearings once .

Size (mm)	15x32x9
Bore Diameter (mm)	15
Outer Diameter (mm)	32
Width (mm)	9
d	15 mm
D	32 mm
B	9 mm
C	9 mm
r min.	0,3 mm
da min.	17 mm
da max	19 mm
Da max.	30 mm
ra max.	0,3 mm
Weight	0,03 Kg
Basic dynamic load rating (C)	5,6 kN
Basic static load rating (C0)	2,83 kN
(Grease) Lubrication Speed	22 000 r/min
(Oil) Lubrication Speed	26 000 r/min
rs min	0.3 mm
Radial clearance class	CN
Mass	0.03 kg

Dynamic load, C	5.6 kN
Static load, C0	2.83 kN
Fatigue limit load, Cu	0.13 kN
f0	13.9
Nlim (oil)	26,000 rpm
Nlim (grease)	22,000 rpm
Min operating temperature, Tmin	-20 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.73 Hz
Characteristic outer ring frequency, BPF0	3.59 Hz
Characteristic inner ring frequency, BRFI	5.41 Hz
da min	17 mm
Da max	30 mm
ra max	0.3 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.03
EAN	4547359003635
Product Group	B00308
Enclosure	Open
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No

Cage Material	Steel
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	15MM Bore; 32MM Outside Diameter; 9MM Outer Race Diameter; Open; Ball Bearing; ABEC 1 ISO P0; No F
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6002
Weight / LBS	0.068
Outside Diameter	1.26 Inch 32 Millimeter
Outer Race Width	0.354 Inch 9 Millimeter
Bore	0.591 Inch 15 Millimeter
bore diameter:	15 mm
finish/coating:	Uncoated
outside diameter:	32 mm
bearing material:	High Carbon Chrome Steel
overall width:	9 mm
cage material:	Steel
bore type:	Round
inner ring width:	9 mm
closure type:	Open
outer ring width:	9 mm

row type & fill slot:	Single Row Non-Fill Slot
maximum rpm (grease):	22000 rpm
snap ring included:	Without Snap Ring
maximum rpm (oil):	26000 rpm
internal clearance:	CN
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	26000 RPM
dynamic load capacity:	5600 N
series:	60
static load capacity:	2830 N
manufacturer product page:	Click here
precision rating:	Class 0