FAG HS71906-C-T-P4S angular contact ball bearings

Offer High Quality Brand FAG HS71906-C-T-P4S angular contact ball bearings .Contact Us 65 mm Shaft Size Online to Get Mounted Bearing Engineering Group Best Quote. Metric Shaft Size Type

| Engineering Group | Mounted Bearing |
|-------------------------|------------------------|
| Shaft Size | 65 mm |
| Shaft Size Type | Metric |
| Full Timken Part Number | TAPG15K065SB |
| Locking Style | Tapered Adapter |
| Weight | 29 lb |
| Housing Style | Four-Bolt Pillow Block |
| UPC Code | 0883450126977 |
| Dimension A | 3.15 in |
| Dimension B | 6.38 in |
| Dimension C | 3.86 in |
| Dimension D Max | 9.69 in |
| Dimension D Min | 7.94 in |
| Dimension E | 1.56 in |
| Dimension F | 10.88 in |
| Dimension G | 3.130 in |
| Dimension H | 1.19 in |
| Dimension J (Bolt Size) | 0.625 in |
| Dimension L | 3.3 in |
| Dimension M | 1.73 in |
| Dimension S | 2.87 in |

| C0 — Static Load | 54100 lb |
|---------------------------------------|-----------|
| C — Dynamic Load (Basic) | 49900 lb |
| e – Geometry Factor | 0.22 |
| Y1 – Geometry Factor | 3.14 |
| Y2 – Geometry Factor | 4.67 |
| Oil Lubrication — M/N Seal | 1600 rpm |
| Oil Lubrication – T Seal | 2900 rpm |
| Oil Lubrication – B/C/O Seal | 1300 rpm |
| Grease Lubrication – M/N Seal | 1600 rpm |
| Grease Lubrication – T Seal | 2400 rpm |
| Grease Lubrication – B/C/O Seal | 1300 rpm |
| Float | 0.083 in |
| Shaft Tolerance | 0.0035 in |
| Pre Install Clearance Min | 0.0037 in |
| Pre Install Clearance Max | 0.0047 in |
| Int Radial Clearance Reduction Min | 0.0015 in |
| Int Radial Clearance Reduction Max | 0.0020 in |
| Adapter Sleeve Axial Movement Min | 0.022 in |
| Adapter Sleeve Axial Movement Max | 0.03 in |
| Post Install Int Radial Clearance Min | 0.0017 in |