

FAG HS71922-E-T-P4S angular contact ball bearings

What are the dimensions of a FAG HS71922-E-T-P4S angular contact ball bearings? Manufacturing 10x19x5 Size (mm) Service . Get Your Free, Instant 19 Outer Diameter (mm) Quote

Size (mm)	10x19x5
Bore Diameter (mm)	10
Outer Diameter (mm)	19
Width (mm)	5
d	10 mm
D	19 mm
B	5 mm
C	5 mm
r min.	0,3 mm
da min.	12 mm
da max	12,5 mm
Da max.	17 mm
ra max.	0,3 mm
Weight	0,005 Kg
Basic dynamic load rating (C)	1,83 kN
Basic static load rating (C0)	0,925 kN
Reference speed	24 000 r/min
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.005
EAN	4547359584950

Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C0-Medium
Inch – Metric	Metric
Long Description	10MM Bore; 19MM Outside Diameter; 5MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; N
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball
Manufacturer Item Number	6800LLU/2AS
Weight / LBS	0.012
Bore	0.394 Inch 10 Millimeter
Outside Diameter	0.748 Inch 19 Millimeter
Outer Race Width	0.197 Inch 5 Millimeter
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Shell Alvania Prelubricat
Inner Race Width	0 Inch 0 Millimeter
bore diameter:	10 mm

precision rating:	ISO Class 0
outside diameter:	19 mm
finish/coating:	Uncoated
overall width:	5 mm
bearing material:	High Carbon Chrome Steel
bore type:	Round
cage material:	Steel
closure type:	Double Sealed
inner ring width:	5 mm
row type & fill slot:	Single Row Non-Fill Slot
outer ring width:	5 mm
snap ring included:	Without Snap Ring
maximum rpm (grease):	24000 rpm
internal clearance:	CN
fillet radius:	0.3 mm
operating temperature range:	-40 to 120 °C
maximum rpm:	24000 RPM
dynamic load capacity:	1830 N
series:	68
static load capacity:	925 N
manufacturer product page:	Click here