

FAG NU2226-E-TVP2 cylindrical roller bearings

FAG NU2226-E-TVP2 cylindrical roller bearings, Units 30 Outer Diameter (mm) and Housings CAD models , Manufacturing Service . Get Your 10x30x9 Size (mm) Free.

Size (mm)	10x30x9
Bore Diameter (mm)	10
Outer Diameter (mm)	30
Width (mm)	9
d	10 mm
D	30 mm
B	9 mm
C	9 mm
Angle (α)	15 °
a –	2.2 mm
r min.	0.6 mm
r1 min.	0.3 mm
2B	18 mm
da min.	15 mm
Da max.	27.4 mm
ra max.	0.3 mm
Weight	0.034 Kg
Basic dynamic load rating (C)	11,3 kN
Basic static load rating (C0)	6,65 kN
(Grease) Lubrication Speed	32000 r/min
Bore Type	Cylindrical Bore
Enclosure	Open

Configuration	Duplex
Bore Size	10 mm
Outside Diameter	30 mm
Width	9 mm
Fillet Radius/Chamfer	0.6 mm
r1	0.3 mm
Dynamic Load Rating	11,300 N
Static Load Rating	6,650 N
Limiting Speed – Grease	32,000 rpm
Limiting Speed – Oil	44,000 rpm
da1 (min)	15 mm
da2 (min)	15 mm
Da1 (max)	25 mm
Da2 (max)	27.4 mm
ra (max)	0.6 mm
ra1 (max)	0.3 mm