

# FAG NUP214-E-TVP2 cylindrical roller bearings

Shop FAG NUP214-E-TVP2 cylindrical roller bearings huge online discount inventory. N/A Minimum Buy Quantity and Import 0.0 Inventory machinery parts your car needs with Free Shipping and Free Extended Warranty.

|                      |   |
|----------------------|---|
| Inventory            | 0.0   |
| Manufacturer Name    | SKF   |
| Minimum Buy Quantity | N/A   |
| Weight               | 0.054   |
| EAN                  | 7316577067104                                 |
| Product Group        | B04270  |
| Enclosure            | Open  |
| Precision Class      | ABEC 7   ISO P4                               |
| Material – Ball      | Steel   |
| Number of Bearings   | 2 (1 Pair)                                    |
| Contact Angle        | 25 Degree                                     |
| Preload              | Light   |
| Raceway Style        | 1 Rib Outer Ring                              |
| Cage Material        | Phenolic                                      |
| Rolling Element      | Ball Bearing                                  |
| Mounting Arrangement | Duplex-Universal                              |
| Flush Ground         | Yes   |
| Inch – Metric        | Metric  |
| Other Features       | Single Row   Angular Contact   High Precision |

|                               |   |
|-------------------------------|---|
| Long Description              | 12MM Bore; 28MM Outside Diameter; 16MM Width; Open Enclosure; ABEC 7   ISO P4 Precision; Steel Ball |
| UNSPSC                        | 31171531  |
| Harmonized Tariff Code        | 8482.10.50.28   |
| Noun                          | Bearing   |
| Keyword String                | Angular Contact Ball  |
| Manufacturer Item Number      | 7001 ACD/P4ADGA   |
| Weight / LBS                  | 0.12  |
| d                             | 0.472 Inch   12 Millimeter  |
| B                             | 0.63 Inch   16 Millimeter   |
| D                             | 1.102 Inch   28 Millimeter  |
| bore diameter:                | 12 mm   |
| radial dynamic load capacity: | 4.36 kN   |
| outside diameter:             | 28 mm   |
| radial static load capacity:  | 1.83 kN   |
| overall width:                | 8 mm  |
| outer ring width:             | 8 mm  |
| contact angle:                | 25 °  |
| maximum rpm:                  | 80000 RPM   |
| row type & fill slot:         | Single-Row Non-Fill Slot  |
| finish/coating:               | Uncoated  |
| internal clearance:           | C0  |
| precision rating:             | ABEC 7 (ISO Class 4)  |
| closure type:                 | Open  |
| fillet radius:                | 0.3 mm  |
| bearing material:             | Steel   |
| series:                       | 70  |