

# FAG NUP2328-E-M1 cylindrical roller bearings

What is the best 0.0 Inventory place to buy FAG NUP2328-E-M1 cylindrical roller bearings online? Manufacturing Service . N/A Minimum Buy Quantity

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | REXNORD  |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 52.66  |
| EAN                       | 0662327414122  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 4  |
| Mounting Method           | Adapter Sleeve   |
| Housing Style             | 4 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 3/4 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | 22224LBC3  |
| Seals                     | Independently Flushable  |
| Housing Configuration     | 2 Piece Split  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   |
| Long Description          | 4 Bolt Pillow Block; 4-3/16" Bore; 5-1/4" Base to Center Height; Adapter Sleeve Mount; Sph |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | PLB6867FD8                      |
| Manufacturer Internal Number  | 5841412                         |
| Weight / LBS                  | 116                             |
| Bolt Spacing Minimum          | 13.25 Inch   336.55Millimeter   |
| D                             | 0 Inch   0 Millimeter           |
| d                             | 4.188 Inch   106.375 Millimeter |
| B                             | 5.25 Inch   133.35 Millimeter   |
| Nominal Bolt Center to Center | 13.9 Inch   353.1 Millimeter    |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| Bolt Spacing Maximum          | 14.5 Inch   368.3Millimeter     |