

# FAG NUP303-E-TVP2 cylindrical roller bearings

Online shopping FAG NUP303-E-TVP2 cylindrical roller bearings from a great selection at 85.725 mm dc Store. ... 90 mm da 104.775 mm db Accessories.

|         |            |
|---------|------------|
| da      | 90 mm      |
| db      | 104.775 mm |
| dc      | 85.725 mm  |
| Da      | 160 mm     |
| Ca      | 49.809 mm  |
| A1      | 98.425 mm  |
| A2      | 149.225 mm |
| ba      | 34.925 mm  |
| H       | 192.484 mm |
| H1      | 101.6 mm   |
| H2      | 41.275 mm  |
| J min.  | 260.35 mm  |
| J max.  | 298.45 mm  |
| L       | 349.25 mm  |
| N1      | 22.225 mm  |
| R1      | 60.325 mm  |
| R2      | 27.781 mm  |
| RG      | 3/8 NPT    |
| PG      | 1/8 NPT    |
| h       | 38.1 mm    |
| Housing | SAF 218    |
| Bearing | 1218       |

|  |                |
|--|----------------|
| Lock nut                               | AN 18          |
| Lock washer                            | W 18           |
| Stabilizing ring                       | 2 x SR-1518    |
| Labyrinth ring (db shaft position)     | LOR 112        |
| Labyrinth ring (dc shaft position)     | LOR 191        |
| End plug (suffix Y)                    | EPR 14         |
| Bearing limiting speed                 | 3800 r/min     |
| P60°                                   | 121 kN         |
| P90°                                   | 72.5 kN        |
| P120°                                  | 45.4 kN        |
| P150°                                  | 40.5 kN        |
| P180°                                  | 49.8 kN        |
| Pa                                     | 32 kN          |
| Mass pillow block                      | 20 kg          |
| Cap bolt                               | 2 x 5/8-11 UNC |
| Cap bolt recommended tightening torque | 149.1 N·m      |
| Cap bolt, SAE grade                    | 5              |
| Appropriate attachment bolt size G     | 0.75 in        |
| Initial grease fill                    | 286.33 g       |