

# FAG S6008 deep groove ball bearings

FAG S6008 deep groove ball bearings manufacturer and global supplier of reliable TIMKEN Manufacturer Name ball and 0.0 Inventory roller ... FAG S6008 deep groove ball bearings Industries Products Manufacturing & Engineering and Agricultural Bearings designed to meet the unique requirements of our targeted industries.

|                           |                          |
|---------------------------|--------------------------|
| Inventory                 | 0.0                      |
| Manufacturer Name         | TIMKEN                   |
| Minimum Buy Quantity      | N/A                      |
| Weight                    | 25.878                   |
| EAN                       | 0883450250764            |
| Product Group             | M06288                   |
| Number of Mounting Holes  | 4                        |
| Mounting Method           | Eccentric Collar         |
| Housing Style             | 4 Bolt Pillow Block      |
| Rolling Element           | Spherical Roller Bearing |
| Housing Material          | Cast Steel               |
| Expansion / Non-expansion | Non-expansion            |
| Mounting Bolts            | 3/4 Inch                 |
| Relubricatable            | Yes                      |
| Insert Part Number        | 22220                    |
| Seals                     | Triple Lip Urethane      |
| Housing Configuration     | 1 Piece Solid            |
| Inch – Metric             | Inch                     |
| Other Features            | Double Row               |

|                               |   |
|-------------------------------|---|
| Long Description              | 4 Bolt Pillow Block; 3-11/16" Bore; 4-1/4" Base to Center Height; Eccentric Collar Mount; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.80   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | QMPF20J311S0  |
| Weight / LBS                  | 67  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| Bolt Spacing Maximum          | 13.38 Inch   339.852Millimeter  |
| D                             | 4.59 Inch   116.586 Millimeter  |
| B                             | 4.25 Inch   107.95 Millimeter   |
| Nominal Bolt Center to Center | 12.5 Inch   317.5 Millimeter  |
| Bolt Spacing Minimum          | 10.875 Inch   276.225Millimeter   |
| d                             | 3.688 Inch   93.675 Millimeter  |