## FBJ 16003ZZ deep groove ball bearings

We 0.0 Inventory Provide N/A Minimum Buy Quantity Extensive FBJ 16003ZZ deep groove ball bearings Selection And Competitive Wholesale Pricing.

| Inventory                 | 0.0   |
|---------------------------|---|
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.435   |
| EAN                       | 0808250248520   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Set Screw   |
| Housing Style             | 4 Bolt Square Flange Block  |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Teflon Coated Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 14 Millimeter   |
| Relubricatable            | Yes   |
| Insert Part Number        | MUC208  |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | No Pilot  |
| Inch — Metric             | Metric  |
| Long Description          | 4 Bolt Square Flange Block;<br>40MM Bore; 144MM Bolt Circle;<br>102MM Bolt Spacing; 1 Piece<br>Solid; Set Scr |

| Other Features                        | Single Row   Spherical  <br>Normal Duty   Has Slinger |
|---------------------------------------|---|
| UNSPSC                                | 31171501  |
| Harmonized Tariff Code                | 8483.20.40.40   |
| Noun                                  | Bearing   |
| Keyword String                        | Flanged   |
| Manufacturer Item Number              | MUCF208TC   |
| Weight / LBS                          | 4.79  |
| Cartridge Pilot Depth                 | 0 Inch   0 Millimeter                                 |
| d                                     | 1.575 Inch   40 Millimeter                            |
| Nominal Bolt Circle Diameter<br>Round | 5.7 Inch   144 Millimeter                             |
| Cartridge Pilot Diameter              | 0 Inch   0 Millimeter                                 |
| D                                     | 1.937 Inch   49.2 Millimeter                          |
| Bolt Spacing                          | 4 Inch   102 Millimeter                               |