

Fersa 33008F tapered roller bearings

What are the types of Fersa 33008F tapered roller bearings 47 Outer Diameter (mm) ? 20x47x17.8 Size (mm) Manufacturing Service . Get Your Free, Instant price, design review.

| | |
|-----------------------------------|------------|
| Size (mm) | 20x47x17.8 |
| Bore Diameter (mm) | 20 |
| Outer Diameter (mm) | 47 |
| Width (mm) | 17,8 |
| D | 47 mm |
| d | 20 mm |
| C | 17.8 mm |
| B | 18 mm |
| D1 | 33 mm |
| F | 25 mm |
| r1,2 – min. | 1 mm |
| r3,4 – min. | 0.3 mm |
| Basic dynamic load rating – C | 16.1 kN |
| Basic static load rating – C0 | 18 kN |
| Fatigue load limit – Pu | 2.2 kN |
| Maximum dynamic radial loads – Fr | 17.6 kN |
| Maximum static radial loads – F0r | 25.5 kN |
| Limiting speed | 4000 r/min |
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.18 |

| | |
|-----------------------------|--|
| EAN | 7316570998849 |
| Product Group | B04144 |
| Roller Surface Profile | Flat |
| Profile | Yoke Type |
| Enclosure | Sealed |
| Rolling Element | Needle Bearing |
| Relubricatable | Yes |
| Inch – Metric | Metric |
| Other Features | Caged With Inner Ring Lip Seal |
| Long Description | 20MM Bore; 47MM Roller Diameter; 17.8MM Roller Width; Flat Roller; Yoke Type; Sealed; Needle Bearing |
| UNSPSC | 31171530 |
| Harmonized Tariff Code | 8482.40.00.00 |
| Noun | Bearing |
| Keyword String | Cam Follower |
| Manufacturer Item Number | NA 2204.2RSX |
| Weight / LBS | 0.397 |
| Bore | 0.787 Inch 20 Millimeter |
| Roller Diameter | 1.85 Inch 47 Millimeter |
| Roller Width | 0.701 Inch 17.8 Millimeter |
| r1,2 min. | 1 mm |
| r3,4 min. | 0.3 mm |
| Basic dynamic load rating C | 16.1 kN |
| Basic static load rating C0 | 18 kN |
| Fatigue load limit Pu | 2.16 kN |

| | |
|--|---------|
| Maximum dynamic radial load $F_{r \max}$. | 17.6 kN |
| Maximum static radial load $F_{0r \max}$. | 25.5 kN |
| Mass support roller | 0.18 kg |