Fersa 33020F tapered roller bearings

Our highly-skilled and factory-trained service experts have the resources ABB MOTORS AND MECHANICAL INC Manufacturer Name to help you with all your Fersa 33020F tapered roller bearings needs — including routine maintenance, major repairs, warranty service, and 0.0 Inventory equipment inspections.

| Inventory | 0.0 |
|---------------------------|---|
| Manufacturer Name | ABB MOTORS AND MECHANICAL INC |
| Minimum Buy Quantity | N/A |
| Weight | 87.622 |
| EAN | 0782475918270 |
| Product Group | M06288 |
| Number of Mounting Holes | 4 |
| Mounting Method | Concentric Collar |
| Housing Style | 4 Bolt Pillow Block |
| Rolling Element | Tapered Roller Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 1 Inch |
| Relubricatable | Yes |
| Insert Part Number | S1U-TAF-500R |
| Seals | Land Riding Rubbing Single Lip Contact |
| Housing Configuration | 2 Piece Split |
| Inch — Metric | Inch |
| Other Features | Double Row Optional E-Tect Seal Double Collar With Set Screw |

| Long Description | 4 Bolt Pillow Block; 5" Bore; 6" Base to Center Height; Concentric Collar Mount; Tapered R |
|----------------------------------|--|
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.80 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | P4B528-TAF-500R |
| Manufacturer Internal Number | 037617 |
| Weight / LBS | 180 |
| В | 6 Inch 152.4 Millimeter |
| D | 7.25 Inch 184.15 Millimeter |
| Bolt Spacing Minimum | 15.625 Inch 396.875Millimeter |
| Bolt Spacing Maximum | 17.375 Inch 441.325Millimeter |
| Actual Bolt Center to Center | 0 Inch OMillimeter |
| Nominal Bolt Center to Center | 16.6 Inch 420.7 Millimeter |
| d | 5 Inch 127 Millimeter |