

# Fersa 387AS/382S tapered roller bearings

High Quality Fersa 387AS/382S tapered roller bearings. Competitive Pricing. 0.0 Inventory Accept Small Order. Easy and Fast Shipping.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REGAL BELOIT  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.68  |
| EAN                       | 0662461254080                                       |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Concentric Collar                                   |
| Housing Style             | 2 Bolt Tap Base Pillow Block                        |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Expansion   |
| Mounting Bolts            | 14 Millimeter                                       |
| Relubricatable            | Yes   |
| Insert Part Number        | 5206TMC   |
| Seals                     | Single Lip Contact                                  |
| Housing Configuration     | 1 Piece Solid                                       |
| Inch – Metric             | Metric  |
| Other Features            | Single Row   Standard Duty   Skwezloc   Has Flinger |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Tap Base Pillow Block;<br>30MM Bore; 42.9MM Base to<br>Center Height; Concentric<br>Collar Mount; Ball |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.40   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | TB-206TMC   |
| Manufacturer Internal Number  | 704173  |
| Weight / LBS                  | 1.7   |
| Actual Bolt Center to Center  | 2.6 Inch   66Millimeter   |
| d                             | 1.181 Inch   30 Millimeter  |
| B                             | 1.689 Inch   42.9 Millimeter  |
| D                             | 1.5 Inch   38.1 Millimeter  |
| Nominal Bolt Center to Center | 2.6 Inch   66 Millimeter  |
| Bolt Spacing Minimum          | 0 Inch   0Millimeter  |
| Bolt Spacing Maximum          | 0 Inch   0Millimeter  |