

# Fersa F19044 cylindrical roller bearings

Fersa F19044 cylindrical roller bearings Needs N/A Minimum Buy Quantity Analysis , Manufacturing Service . Get 0.0 Inventory Your Free.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | ASAHI BEARINGS  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.87  |
| EAN                       | 0808250322756   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 4   |
| Mounting Method           | Set Screw   |
| Housing Style             | 4 Bolt Round Flange Cartridge   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Teflon Coated Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 3/8 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | UC208-24  |
| Seals                     | Contact Seal  |
| Housing Configuration     | 1 Piece Solid   |
| Pilot Configuration       | With Pilot  |
| Inch – Metric             | Inch  |
| Long Description          | 4 Bolt Round Flange Cartridge;<br>1-1/2" Bore; 4.4" Bolt Circle;<br>3.1" Bolt Spacing; 1 Pi |

|                                    |  |
|------------------------------------|--|
| Other Features                     | Single Row   Spherical   Normal Duty   Has Slinger |
| UNSPSC                             | 31171501   |
| Harmonized Tariff Code             | 8483.20.40.40                                      |
| Noun                               | Bearing  |
| Keyword String                     | Flanged  |
| Weight / LBS                       | 3.71   |
| Nominal Bolt Circle Diameter Round | 4.4 Inch   111 Millimeter                          |
| Cartridge Pilot Diameter           | 3.625 Inch   92.08 Millimeter                      |
| d                                  | 1.5 Inch   38.1 Millimeter                         |
| Cartridge Pilot Depth              | 0.438 Inch   11.125 Millimeter                     |
| Bolt Spacing                       | 3.1 Inch   78.5 Millimeter                         |
| D                                  | 1.937 Inch   49.2 Millimeter                       |