

Fersa M88046/M88010 tapered roller bearings

offers a Fersa M88046/M88010 tapered roller bearings selection of Genuine at Wholesale Prices. We are a Fersa M88046/M88010 tapered roller bearings Certified 35 mm d Parts Retailer

d	35 mm
D	72 mm
B	17 mm
rs min	1.1 mm
Radial clearance class	C2
Mass	0.29 kg
Dynamic load, C	25.7 kN
Static load, C ₀	15.3 kN
Fatigue limit load, C _u	0.7 kN
f ₀	13.8
N _{lim} (grease)	6,300 rpm
Min operating temperature, T _{min}	-25 °C
Max operating temperature, T _{max}	110 °C
Characteristic cage frequency, FTF	0.4 Hz
Characteristic rolling element frequency, BSF	4.61 Hz
Characteristic outer ring frequency, BPF ₀	3.56 Hz
Characteristic inner ring frequency, BRFI	5.44 Hz
da min	41.5 mm
da max	45 mm

Da max	65.5 mm
ra max	1 mm
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.285
Product Group	B00308
Enclosure	2 Seals
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C2-Snug
Inch – Metric	Metric
Long Description	35MM Bore; 72MM Outside Diameter; 17MM Outer Race Width; 2 Seals; Ball Bearing; ABEC 1 ISO P0; No
Other Features	Deep Groove Double Lip Friction Nitrile Rubber Seal -20 To 120 Deg C Prelubricated
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing
Keyword String	Ball

Weight / LBS	0.635
Inner Race Width	0 Inch 0 Millimeter
Bore	1.378 Inch 35 Millimeter
Outside Diameter	2.835 Inch 72 Millimeter
Outer Race Width	0.669 Inch 17 Millimeter