

Flexible High Speed Gear Drive Double Pinion Drive Spur Gear Slewing Drive for Antenna Positioner

Flexible High Speed Gear Drive Double Pinion Drive Spur Gear Slewing Drive for Antenna Positioner Needs Analysis , 0.0
Inventory IPTCI BEARINGS Manufacturer Name Manufacturing N/A
Minimum Buy Quantity Service . Get Your Free.

| | |
|---------------------------|----------------------------|
| Inventory | 0.0 |
| Manufacturer Name | IPTCI BEARINGS |
| Minimum Buy Quantity | N/A |
| Weight | 5.86 |
| Product Group | M06110 |
| Number of Mounting Holes | 4 |
| Mounting Method | Set Screw |
| Housing Style | 4 Bolt Square Flange Block |
| Rolling Element | Ball Bearing |
| Housing Material | Nickel Coated Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 5/8 Inch |
| Relubricatable | Yes |
| Insert Part Number | BUC213-40 |
| Seals | B Seal |
| Housing Configuration | 1 Piece Solid |
| Pilot Configuration | No Pilot |
| Inch – Metric | Inch |

| | |
|---------------------------------------|---|
| Long Description | 4 Bolt Square Flange Block; 2-1/2" Bore; 8.3" Bolt Circle; 5-7/8" Bolt Spacing; 1 Pie |
| Other Features | Single Row Spherical Corrosion Resistant Black Oxide Insert |
| UNSPSC | 31171501 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Flanged |
| Manufacturer Item Number | BUCNPF 213 40 |
| Weight / LBS | 12.9 |
| d | 2.5 Inch 63.5 Millimeter |
| Cartridge Pilot Depth | 0 Inch 0 Millimeter |
| Bolt Spacing | 5.875 Inch 149.225 Millimeter |
| Cartridge Pilot Diameter | 0 Inch 0 Millimeter |
| Nominal Bolt Circle Diameter Round | 8.3 Inch 211 Millimeter |
| D | 2.563 Inch 65.09 Millimeter |