

# FYH UCF215 bearing units

How do I place an EMERGENCY order for a 117.805 mm Ca FYH UCF215 bearing units 200.025 mm da that I want to pick up at a 399.999 mm Da our store?

da	200.025 mm
Da	399.999 mm
Ca	117.805 mm
A1	222.25 mm
A2	304.8 mm
S	4.763 mm
ba	90.487 mm
H	474.663 mm
H1	241.3 mm
H2	95.25 mm
J min.	628.65 mm
J max.	708.025 mm
J1	133.35 mm
L	831.85 mm
N1	41.275 mm
R1	130.175 mm
R2	46.831 mm
RG	1 NPT
PG	1/4 NPT
h	79.375 mm
Housing	SAF 544
Bearing	22244 CCK/W33
Adapter sleeve assembly	SNW 44×7.7/8

Stabilizing ring	SR-44-38
Labyrinth ring	2 x LOR 166
End plug (suffix Y)	EPR 23
Bearing limiting speed	2000 r/min
P60°	423 kN
P90°	254 kN
P120°	160 kN
P150°	145 kN
P180°	173 kN
Pa	71.2 kN
Mass pillow block	262 kg
Cap bolt	4 x 1-8 UNC
Cap bolt recommended tightening torque	400 N·m
Cap bolt, SAE grade	5
Eye bolt	2 x 1/2-13 UNC
Appropriate attachment bolt size G	1.5 in
Initial grease fill	2749.95 g