

FYH UCFL215-48 bearing units

Browse FYH UCFL215-48 bearing units Categories in 40,000 Bore Diameter (mm) the Manufacturers 40x55x40 Size (mm) Online Free. including . 55,000 Outer Diameter (mm)

| | |
|------------------------------------|------------|
| Size (mm) | 40x55x40 |
| Bore Diameter (mm) | 40,000 |
| Outer Diameter (mm) | 55,000 |
| Width (mm) | 40,000 |
| Fw | 40,000 mm |
| D | 55,000 mm |
| C | 40,000 mm |
| E | 48 mm |
| rs min | 0.3 mm |
| Dw | 3.5 mm |
| Lw | 15.8 mm |
| Lubrication hole on outer ring | Oui/Yes |
| k | 3 mm |
| Radial clearance class | CN |
| Precision class | P0 |
| Mass | 0.28 kg |
| Cr | 56.5 kN |
| C0r | 102 kN |
| Nlim (grease) | 6,500 rpm |
| Nlim (oil) | 10,000 rpm |
| Min operating temperature, Tmin | -20 °C |
| Max operating temperature, Tmax | 120 °C |
| Characteristic cage frequency, FTF | 0.46 Hz |

| | |
|---|----------|
| Characteristic rolling element frequency, BSF | 12.35 Hz |
| Characteristic outer ring frequency, BPF0 | 11.03 Hz |
| Characteristic inner ring frequency, BRFI | 12.97 Hz |
| db | 47.2 mm |
| Da max | 53 mm |
| Db | 40.6 mm |
| ras max | 0.3 mm |