

FYH UCFS320-64 bearing units

FYH UCFS320-64 bearing units SEARCH – Whether it's agriculture or construction equipment your working on, Has the 260x105x60 Size (mm) you need.

| | |
|-------------------------------|------------|
| Size (mm) | 260x105x60 |
| Bore Diameter (mm) | 260 |
| Outer Diameter (mm) | 105 |
| Width (mm) | 60 |
| d | 105 mm |
| D | 260 mm |
| B | 60 mm |
| D1 | 206.3 mm |
| F | 144.5 mm |
| r1,2 – min. | 4 mm |
| r3,4 – min. | 4 mm |
| s | 4.9 mm |
| da – min. | 124 mm |
| da – max. | 140 mm |
| db – min. | 147 mm |
| Da – max. | 241 mm |
| ra – max. | 3 mm |
| rb – max. | 3 mm |
| Basic dynamic load rating – C | 501 kN |
| Basic static load rating – C0 | 570 kN |
| Fatigue load limit – Pu | 64 kN |
| Reference speed | 2800 r/min |
| Limiting speed | 3400 r/min |

| | |
|--------------------------------|----------|
| Calculation factor – k_r | 0.15 |
| $D_1 \approx$ | 206.3 mm |
| $r_{1,2} \text{ min.}$ | 4 mm |
| $r_{3,4} \text{ min.}$ | 4 mm |
| $s \text{ max.}$ | 4.9 mm |
| $d_a \text{ min.}$ | 124 mm |
| $d_a \text{ max.}$ | 140 mm |
| $d_b \text{ min.}$ | 147 mm |
| $D_a \text{ max.}$ | 241 mm |
| $r_a \text{ max.}$ | 3 mm |
| $r_b \text{ max.}$ | 3 mm |
| Basic dynamic load rating C | 501 kN |
| Basic static load rating C_0 | 570 kN |
| Fatigue load limit P_u | 64 kN |
| Calculation factor k_r | 0.15 |
| Limiting value e | 0.2 |
| Axial load factor Y | 0.6 |
| Mass bearing | 17.3 kg |