

# Gamet 160090/160158XH tapered roller bearings

Enjoy High Margins on Competitive 104.775 mm da Pricing.Great 55.804 mm Ca Wholesale Products at Low 180 mm Da Costs.

da	104.775 mm
Da	180 mm
Ca	55.804 mm
A1	111.125 mm
A2	155.575 mm
ba	46.831 mm
H	222.25 mm
H1	114.3 mm
H2	44.45 mm
J min.	295.275 mm
J max.	333.375 mm
L	387.35 mm
N1	26.988 mm
R1	65.088 mm
R2	30.163 mm
RG	3/8 NPT
PG	1/4 NPT
h	40.481 mm
Housing	SAFS 024 KA
Bearing	23024 CCK/W33
Adapter sleeve assembly	SNW 3024×4.1/8
Stabilizing ring	2 x 38151-24
Labyrinth ring	2 x LOR 112

End plug (suffix Y)	EPR 14
Bearing limiting speed	4000 r/min
P60°	141 kN
P90°	84.5 kN
P120°	52.5 kN
P150°	48 kN
P180°	57.4 kN
Pa	16.7 kN
Mass pillow block	39 kg
Cap bolt	5/8-11 UNC
Cap bolt recommended tightening torque	298.3 N·m
Cap bolt, SAE grade	8
Appropriate attachment bolt size G	0.875 in
Initial grease fill	181.44 g