

Gamet 203156/203235 tapered roller bearings

What 36,513 mm d are the 29.4 mm s1 dimensions 36,513 Bore Diameter (mm) of a Gamet 203156/203235 tapered roller bearings? Manufacturing Service . Get Your Free, Instant Quote

Bore Diameter (mm)	36,513
d	36,513 mm
s1	29.4 mm
A1	13 mm
B1	38.9 mm
G	12 mm
J	92 mm
L	118 mm
T	50,4 mm
A2	13 mm
Weight	1,45 Kg
Basic dynamic load rating (C)	25,5 kN
Basic static load rating (C0)	15,3 kN
Fatigue load limit (Pu)	0,655
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	1.5
EAN	7316576614484
Product Group	M06110
Number of Mounting Holes	4

Mounting Method	Eccentric Collar
Housing Style	4 Bolt Square Flange Block
Rolling Element	Ball Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Insert Part Number	YET 207-107
Seals	M Seal
Housing Configuration	1 Piece Solid
Pilot Configuration	No Pilot
Inch – Metric	Inch
Long Description	4 Bolt Square Flange Block; 1-7/16" Bore; 5.1" Bolt Circle; 3-5/8" Bolt Spacing; 1 Pi
Other Features	Single Row Standard Duty Narrow Inner Race Open End Y Bearing
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.40
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	FY 1.7/16 FM
Weight / LBS	3.31
Bore	1.438 Inch 36.525 Millimeter
Nominal Bolt Circle Diameter Round	5.1 Inch 130 Millimeter
Cartridge Pilot Diameter	0 Inch 0 Millimeter

Cartridge Pilot Depth	0 Inch 0 Millimeter
Bolt Spacing	3.625 Inch 92.08 Millimeter
Length Thru Bore	1.531 Inch 38.9 Millimeter
Housing material	Cast iron
Da	106.4 mm
Db1	87 mm
Db2	95 mm
A	34.5 mm
A3	3.2 mm
A5	24.5 mm
N	14 mm
RG	1/4-28 UNF
R1	22.5 mm
DN	6.5 mm
SWN	7 mm
GN	1/4-28 SAE-LT
J6	106 mm
J7	29 mm
N4	4 mm
Basic dynamic load rating C	25.5 kN
Basic static load rating C0	15.3 kN
Fatigue load limit Pu	0.655 kN
Limiting speed	5300 r/min
Mass bearing unit	1.3 kg
Thread grub screw G2	3/8-24 UNF
Hexagonal key size for grub screw N	4.763 mm
Recommended tightening torque for grub screw	16.5 N·m

Recommended diameter for attachment bolts, mm G	12 mm
Recommended diameter for attachment bolts, inch G	0.5 in
Housing	FY 507 M
Bearing	YET 207-107
End cover	ECY 207