## Gamet 380330X/380482XC tapered roller bearings

Gamet 380330X/380482XC tapered roller bearings Product Brochures , N/A Minimum Buy Quantity 0.0 Inventory Manufacturing Service . REGAL BELOIT Manufacturer Name Get Your Free.

| Inventory                 | 0.0  |
|---------------------------|--|
| Manufacturer Name         | REGAL BELOIT   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 2.268  |
| EAN                       | 0662798248042  |
| Product Group             | M06110   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | Set Screw  |
| Housing Style             | 2 Bolt Pillow Block                                    |
| Rolling Element           | Ball Bearing   |
| Housing Material          | Cast Iron  |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 1/2 Inch   |
| Relubricatable            | Yes  |
| Insert Part Number        | B250   |
| Seals                     | Nitrile Rubber   |
| Housing Configuration     | 1 Piece Solid  |
| Inch — Metric             | Inch   |
| Other Features            | Single Row   Spherical   Low<br>Base   Has Trash Guard |

| Long Description                 | 2 Bolt Pillow Block; 1-1/2"<br>Bore; 1-15/16" Base to Center<br>Height; Set Screw Mount; Ball Be |
|----------------------------------|--|
| UNSPSC                           | 31171511   |
| Harmonized Tariff Code           | 8483.20.40.40  |
| Noun                             | Bearing  |
| Keyword String                   | Pillow Block   |
| Manufacturer Item Number         | 1001-00918   |
| Manufacturer Internal Number     | 24804  |
| Weight / LBS                     | 4.5  |
| Nominal Bolt Center to<br>Center | 5.5 Inch   140 Millimeter  |
| Bolt Spacing Maximum             | 5.938 Inch   150.825Millimeter   |
| Actual Bolt Center to Center     | 0 Inch   OMillimeter   |
| d                                | 1.5 Inch   38.1 Millimeter   |
| В                                | 1.938 Inch   49.225 Millimeter   |
| D                                | 1.575 Inch   40 Millimeter   |
| Bolt Spacing Minimum             | 5.125 Inch   130.2Millimeter   |