

Gamet 70030/70062 tapered roller bearings

Welcome to the Gamet 70030/70062 tapered roller bearings 52.375 mm dc online 55 mm da seller. 65.075 mm db

| | |
|---------|------------|
| da | 55 mm |
| db | 65.075 mm |
| dc | 52.375 mm |
| Da | 120 mm |
| Ca | 52.807 mm |
| A1 | 79.375 mm |
| A2 | 196.85 mm |
| ba | 29.369 mm |
| H | 157.162 mm |
| H1 | 82.55 mm |
| H2 | 30.163 mm |
| J min. | 206.375 mm |
| J max. | 241.3 mm |
| J1 | 50.8 mm |
| L | 279.4 mm |
| N1 | 15.875 mm |
| R1 | 44.45 mm |
| R2 | 25.4 mm |
| RG | 1/8 NPT |
| PG | 1/8 NPT |
| h | 38.1 mm |
| Housing | FSAF 311 |
| Bearing | 1311 ETN9 |

| | |
|--|----------------|
| Lock nut | AN 20 |
| Lock washer | W 11 |
| Stabilizing ring | 2 x SR-1611 |
| Taconite seal (db shaft position) | TER 40 |
| Taconite seal (dc shaft position) | TER 27 |
| End plug (suffix Y) | EPR 6 |
| Max. speed for Taconite seal | 1200 r/min |
| P60° | 35.6 kN |
| P90° | 21.4 kN |
| P120° | 13.3 kN |
| P150° | 12 kN |
| P180° | 14.2 kN |
| Pa | 9.34 kN |
| Mass pillow block | 11.4 kg |
| Cap bolt | 2 x 1/2-13 UNC |
| Cap bolt recommended tightening torque | 149.1 N·m |
| Cap bolt, SAE grade | 8 |
| Appropriate attachment bolt size G | 0.5 in |
| Initial grease fill | 68.04 g |