

# IKO BA 1516 Z needle roller bearings

LET OUR IKO BA 1516 Z needle roller bearings EXPERTS TIMKEN Manufacturer Name GET YOU THE PARTS 0.0 Inventory YOU NEED.

|                           |  |
|---------------------------|--|
| Inventory                 | 0.0  |
| Manufacturer Name         | TIMKEN   |
| Minimum Buy Quantity      | N/A  |
| Weight                    | 31.326   |
| EAN                       | 0883450230162  |
| Product Group             | M06288   |
| Number of Mounting Holes  | 2  |
| Mounting Method           | V Lock   |
| Housing Style             | 2 Bolt Pillow Block  |
| Rolling Element           | Spherical Roller Bearing   |
| Housing Material          | Cast Steel   |
| Expansion / Non-expansion | Non-expansion  |
| Mounting Bolts            | 24 Millimeter  |
| Relubricatable            | Yes  |
| Insert Part Number        | 22222  |
| Seals                     | Triple Lip Urethane  |
| Housing Configuration     | 1 Piece Solid  |
| Inch – Metric             | Inch   |
| Other Features            | Double Row   Double Nut   SN Style   |
| Long Description          | 2 Bolt Pillow Block; 3-15/16" Bore; 4-59/64" Base to Center Height; V Lock Mount; Spherica |

|                               |                                 |
|-------------------------------|---------------------------------|
| UNSPSC                        | 31171511                        |
| Harmonized Tariff Code        | 8483.20.40.80                   |
| Noun                          | Bearing                         |
| Keyword String                | Pillow Block                    |
| Manufacturer Item Number      | QVVSN22V315S0                   |
| Weight / LBS                  | 79                              |
| B                             | 4.921 Inch   125 Millimeter     |
| Bolt Spacing Maximum          | 14.409 Inch   366Millimeter     |
| Nominal Bolt Center to Center | 13.5 Inch   342.5 Millimeter    |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter            |
| d                             | 3.938 Inch   100.025 Millimeter |
| D                             | 5.118 Inch   130 Millimeter     |
| Bolt Spacing Minimum          | 12.559 Inch   319Millimeter     |