

# IKO BAM 128 needle roller bearings

We Provide 125.412 mm dc Extensive IKO BAM 128 needle roller bearings 130 mm da 149.225 mm db Selection And Competitive Wholesale Pricing.

da	130 mm
db	149.225 mm
dc	125.412 mm
Da	230 mm
Ca	73.787 mm
A1	130.175 mm
A2	203.2 mm
S	4.763 mm
ba	57.944 mm
H	292.1 mm
H1	152.4 mm
H2	60.325 mm
L	466.725 mm
R1	79.375 mm
R2	36.513 mm
RG	1/2 NPT
PG	1/4 NPT
h	59.531 mm
Housing	SSAFS 226
Bearing	22226 E
Lock nut	AN 26
Lock washer	W 26

Stabilizing ring	SR-26-0
Labyrinth ring (db shaft position)	LOR 136
PosiTrac Plus contact element (db shaft position)	B10724-134
Labyrinth ring (dc shaft position)	LOR 122
PosiTrac Plus contact element (dc shaft position)	B10724-122
End plug (suffix Y)	EPR 27
Max. speed for PosiTrac Plus seal	980 r/min
P60°	308 kN
P90°	185 kN
P120°	125 kN
P150°	118 kN
P180°	151 kN
Pa	98.3 kN
Mass pillow block	81.2 kg
Cap bolt	3/4-10 UNC
Cap bolt recommended tightening torque	515.2 N·m
Cap bolt, SAE grade	8
Eye bolt	3/8-16 UNC
Initial grease fill	765.45 g