

IKO BAM 2816 needle roller bearings

Advance IKO BAM 2816 needle roller bearings is your source 110 Outer Diameter (mm) for quality and accessories. 50 Bore Diameter (mm) shop online for home delivery or pick up in one of our 10000 . 50x110x29.25 Size (mm)

Size (mm)	50x110x29.25
Bore Diameter (mm)	50
Outer Diameter (mm)	110
Width (mm)	29,25
d	50 mm
D	110 mm
T	29,25 mm
B	27 mm
C	23 mm
a	23,1 mm
r min.	2,5 mm
r1 min.	2 mm
da min.	65 mm
Da min	95 mm
Da max.	100 mm
db max.	65 mm
Db min.	102 mm
ra max.	2 mm
rb max.	2 mm
Weight	1,28 Kg
Basic dynamic load rating (C)	130 kN

Basic static load rating (C0)	148 kN
(Grease) Lubrication Speed	3400 r/min
(Oil) Lubrication Speed	4800 r/min
Calculation factor (e)	0,35
Calculation factor (Y0)	0,96
LangID	1
outer r	2
D_	110
TC-BET22	0
TC-BET21	4
TC-BET23	0
inner r	2.5
mass	1.28
GRS rpm	3400
D_b	102
Cr	13300
TC-RA	224
DE_	95.923
T-ALP23	20
db	65
T-ALP22	54
Prod_Type3	TRBSR_MD_A
da	65
T-ALP21	25
Iso	2FB
ALPHA_	12.953
SDM_	81.334
SBRG	3
D_a2	95

hidYobi	HR30310J
Y1	1.7
D_a1	100
B_	27
hidTable	ecat_NSTPRM
Oil rpm	4800
C0r	15100
Y0	0.96
TC-SLR	19
inner ra	2
outer rb	2
C0	148
Sa	3
Sb	6
e	0.35
DA_	14.976
Z_	16
C_	23
yobi	HR30310J
TC-DA1	15.634
TC-DA2	14.318
KBRG	3111
DI_	66.745