## IKO BAM 95 needle roller bearings

How do I place an EMERGENCY order for 6  $^{\circ}$  misalignment angle: a IKO BAM 95 needle roller bearings that 0.3750 in d I want to pick up at a our store?

| d                            | 0.3750 in                                  |
|------------------------------|--|
| radial static load capacity: | 2950 lb                                    |
| misalignment angle:          | 6 °  |
| axial static load capacity:  | 295 lb                                     |
| shank thread length:         | 1.2190 in                                  |
| lubrication:                 | Self Lubricating                           |
| rod end type:                | Male Threaded                              |
| operating temperature range: | Max 250°                                   |
| shank thread size:           | 3/8-24 in                                  |
| head diameter:               | 1.0000 in                                  |
| thread direction:            | Left Hand                                  |
| head width:                  | .4060 in                                   |
| grade:                       | Precision                                  |
| ball width:                  | .5000 in                                   |
| lubrication type:            | Self Lubricating                           |
| length to ball center:       | 1.9380 in                                  |
| housing material:            | Carbon Steel — corrosion resistant plating |
| series:                      | CFM-T                                      |
| ball material:               | Alloy Steel — heat treated — chrome plated |
| manufacturer catalog number: | 1580604000                                 |

| race material:   IEFLUN | race material: | TEFLON |
|-------------------------|----------------|--------|
|-------------------------|----------------|--------|