

IKO BHA 2020 Z needle roller bearings

Find 40x62x12 Size (mm) the discount IKO BHA 2020 Z needle roller bearings online you need . We offer ... If you check 40 Bore Diameter (mm) out our large selection of IKO BHA 2020 Z needle roller bearings once .

| | |
|-------------------------------|--------------|
| Size (mm) | 40x62x12 |
| Bore Diameter (mm) | 40 |
| Outer Diameter (mm) | 62 |
| Width (mm) | 12 |
| d | 40 mm |
| D | 62 mm |
| B | 12 mm |
| C | 12 mm |
| r min. | 0,6 mm |
| da min. | 44 mm |
| da max | 45 mm |
| Da max. | 58 mm |
| ra max. | 0,6 mm |
| Weight | 0,11 Kg |
| Basic dynamic load rating (C) | 12,2 kN |
| Basic static load rating (C0) | 8,9 kN |
| (Grease) Lubrication Speed | 11 000 r/min |
| Inventory | 0.0 |
| Manufacturer Name | NTN |
| Minimum Buy Quantity | N/A |
| Weight / Kilogram | 0.109 |

| | |
|---------------------------------|---|
| Product Group | B00308 |
| Enclosure | 2 Seals |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Rolling Element | Ball Bearing |
| Snap Ring | No |
| Internal Special Features | No |
| Cage Material | Steel |
| Enclosure Type | Non-Contact Seal |
| Internal Clearance | C0-Medium |
| Inch – Metric | Metric |
| Long Description | 40MM Bore; 62MM Outside Diameter; 12MM Outer Race Diameter; 2 Seals; Ball Bearing; ABEC 1 ISO P0; |
| UNSPSC | 31171504 |
| Harmonized Tariff Code | 8482.10.50.68 |
| Noun | Bearing |
| Keyword String | Ball |
| Manufacturer Item Number | 6908LLB/2AS |
| Weight / LBS | 0.241 |
| Bore | 1.575 Inch 40 Millimeter |
| Outer Race Width | 0.472 Inch 12 Millimeter |
| Outside Diameter | 2.441 Inch 62 Millimeter |
| bore diameter: | 40 mm |
| precision rating: | ISO Class 0 |
| outside diameter: | 62 mm |
| finish/coating: | Uncoated |
| overall width: | 12 mm |
| bearing material: | High Carbon Chrome Steel |

| | |
|------------------------------|----------------------------|
| bore type: | Round |
| cage material: | Steel |
| closure type: | Double Sealed |
| inner ring width: | 12 mm |
| row type & fill slot: | Single Row Non-Fill Slot |
| outer ring width: | 12 mm |
| snap ring included: | Without Snap Ring |
| maximum rpm (grease): | 11000 rpm |
| internal clearance: | CN |
| fillet radius: | 0.6 mm |
| operating temperature range: | -40 to 120 °C |
| maximum rpm: | 11000 RPM |
| dynamic load capacity: | 12200 N |
| series: | 69 |
| static load capacity: | 8900 N |
| manufacturer product page: | Click here |