

IKO BRI 243920 U needle roller bearings

170 Million used 0.0 Inventory N/A Minimum Buy Quantity IKO BRI 243920 U needle roller bearings instantly searchable. Shop SKF Manufacturer Name our large selection of parts based on brand, price, description, and location. Order the with stock ...

| | |
|---------------------------------|-----------------|
| Inventory | 0.0 |
| Manufacturer Name | SKF |
| Minimum Buy Quantity | N/A |
| Weight | 0.063 |
| EAN | 7316571314624 |
| Product Group | B00152 |
| Enclosure | Open |
| Flush Ground | No |
| Rolling Element | Ball Bearing |
| Number of Rows of Balls | Double Row |
| Precision Class | ABEC 1 ISO P0 |
| Maximum Capacity / Filling Slot | No |
| Snap Ring | No |
| Cage Material | Polyamide |
| Contact Angle | 30 Degree |
| Internal Clearance | C3-Loose |
| Number of Bearings | 1 (Single) |
| Inch – Metric | Metric |

| | |
|-------------------------------|--|
| Long Description | 12MM Bore; 32MM Outside Diameter; 15.9MM Width; Open; No Flush Ground; Ball Bearing; Double Row of B |
| Other Features | Glass Fibre Reinforced Cage |
| UNSPSC | 31171531 |
| Harmonized Tariff Code | 8482.10.50.28 |
| Noun | Bearing |
| Keyword String | Angular Contact |
| Manufacturer Item Number | 3201 ATN9/C3 |
| Weight / LBS | 0.1377 |
| D | 1.26 Inch 32 Millimeter |
| d | 0.472 Inch 12 Millimeter |
| B | 0.626 Inch 15.9 Millimeter |
| bore diameter: | 12 mm |
| radial static load capacity: | 5.6 kN |
| outside diameter: | 32 mm |
| cage material: | Polyamide |
| overall width: | 0.6250 in |
| outer ring width: | 15.9 mm |
| contact angle: | 30 ° |
| maximum rpm: | 22000 RPM |
| row type & fill slot: | Double-Row Non-Fill Slot |
| finish/coating: | Uncoated |
| internal clearance: | C3 |
| precision rating: | Not Rated |
| closure type: | Open |
| fillet radius: | 0.6 mm |
| radial dynamic load capacity: | 10.1 kN |
| series: | 32 |