

# IKO CRBC 40040 thrust roller bearings

Advance IKO CRBC 40040 thrust roller bearings is your source for quality and accessories. 254 Outer Diameter (mm) shop online for home delivery or pick up in one 533.4x254x133.35 Size (mm) of our 10000 .

|                     |                  |
|---------------------|------------------|
| Size (mm)           | 533.4x254x133.35 |
| Bore Diameter (mm)  | 533,4            |
| Outer Diameter (mm) | 254              |
| Width (mm)          | 133,35           |
| d                   | 254 mm           |
| D                   | 533.4 mm         |
| T                   | 133.35 mm        |
| d1                  | 390 mm           |
| B                   | 120.65 mm        |
| C                   | 77.788 mm        |
| r1,2 – min.         | 6.4 mm           |
| r3,4 – min.         | 6.4 mm           |
| a                   | 164 mm           |
| da – max.           | 300 mm           |
| db – min.           | 286 mm           |
| Da – min.           | 420 mm           |
| Da – max.           | 502 mm           |
| Db – min.           | 501 mm           |
| Ca – min.           | 14 mm            |
| Cb – min.           | 55 mm            |
| ra – max.           | 6 mm             |

|                               |            |
|-------------------------------|------------|
| rb – max.                     | 6 mm       |
| Basic dynamic load rating – C | 2090 kN    |
| Basic static load rating – C0 | 2900 kN    |
| Fatigue load limit – Pu       | 240 kN     |
| Reference speed               | 800 r/min  |
| Limiting speed                | 1100 r/min |
| Calculation factor – e        | 0.88       |
| Calculation factor – Y        | 0.68       |
| Calculation factor – Y0       | 0.4        |
| d1 ≈                          | 389.5 mm   |
| r1,2 min.                     | 6.4 mm     |
| r3,4 min.                     | 6.4 mm     |
| da max.                       | 300 mm     |
| db min.                       | 286 mm     |
| Da min.                       | 420 mm     |
| Da max.                       | 502 mm     |
| Db min.                       | 501 mm     |
| Ca min.                       | 8 mm       |
| Cb min.                       | 55 mm      |
| ra max.                       | 6 mm       |
| rb max.                       | 6 mm       |
| Basic dynamic load rating C   | 2090 kN    |
| Basic static load rating C0   | 2900 kN    |
| Fatigue load limit Pu         | 240 kN     |
| Calculation factor e          | 0.88       |
| Calculation factor Y          | 0.68       |
| Calculation factor Y0         | 0.4        |
| Mass bearing                  | 120 kg     |