

# IK0 CRBF 5515 AT thrust roller bearings

With over 10170 full-service stores, our IK0 CRBF 5515 AT thrust roller bearings inventory is extensive and our parts are priced right. within 24 hours. This helps you maximize your 0.0 Inventory productivity by saving time and your hard-earned dollars.

|                           |   |
|---------------------------|---|
| Inventory                 | 0.0   |
| Manufacturer Name         | REGAL BELOIT  |
| Minimum Buy Quantity      | N/A   |
| Weight                    | 1.32  |
| EAN                       | 0662798247724   |
| Product Group             | M06110  |
| Number of Mounting Holes  | 2   |
| Mounting Method           | Eccentric Collar  |
| Housing Style             | 2 Bolt Pillow Block   |
| Rolling Element           | Ball Bearing  |
| Housing Material          | Cast Iron   |
| Expansion / Non-expansion | Non-expansion   |
| Mounting Bolts            | 1/2 Inch  |
| Relubricatable            | Yes   |
| Insert Part Number        | B220  |
| Seals                     | Nitrile Rubber  |
| Housing Configuration     | 1 Piece Solid   |
| Inch – Metric             | Inch  |
| Other Features            | Single Row   Spherical   High Base   Has Trash Guard   With Set Screw |

|                               |   |
|-------------------------------|---|
| Long Description              | 2 Bolt Pillow Block; 1-1/8" Bore; 1-11/16" Base to Center Height; Eccentric Collar Mount; |
| UNSPSC                        | 31171511  |
| Harmonized Tariff Code        | 8483.20.40.40   |
| Noun                          | Bearing   |
| Keyword String                | Pillow Block  |
| Manufacturer Item Number      | 1001-00811  |
| Manufacturer Internal Number  | 24772   |
| Weight / LBS                  | 2.9   |
| Nominal Bolt Center to Center | 4.8 Inch   121 Millimeter   |
| Bolt Spacing Maximum          | 5.125 Inch   130.175Millimeter  |
| d                             | 1.125 Inch   28.575 Millimeter  |
| Actual Bolt Center to Center  | 0 Inch   0Millimeter  |
| B                             | 1.688 Inch   42.875 Millimeter  |
| Bolt Spacing Minimum          | 4.25 Inch   107.95Millimeter  |
| D                             | 1.406 Inch   35.7 Millimeter  |