IKO CRBS 908 V UU thrust roller bearings

IKO CRBS 908 V UU thrust roller bearings SEARCH – Whether it's agriculture ASAHI BEARINGS Manufacturer Name or construction equipment your working on, Has the 0.0 Inventory you need.

| Inventory | 0.0 |
|---------------------------|---|
| Manufacturer Name | ASAHI BEARINGS |
| Minimum Buy Quantity | N/A |
| Weight | 7.99 |
| EAN | 0808250274840 |
| Product Group | M06110 |
| Number of Mounting Holes | 2 |
| Mounting Method | Set Screw |
| Housing Style | 2 Bolt Pillow Block |
| Rolling Element | Ball Bearing |
| Housing Material | Cast Iron |
| Expansion / Non-expansion | Non-expansion |
| Mounting Bolts | 20 Millimeter |
| Relubricatable | Yes |
| Insert Part Number | UC215C4HR23 |
| Seals | Contact Seal |
| Housing Configuration | 1 Piece Solid |
| Inch — Metric | Metric |
| Other Features | Single Row Spherical Normal Duty High Temperature Range Up to 450 Degree F Has Slinger |

| Long Description | 2 Bolt Pillow Block; 75MM Bore; 82.6MM Base to Center Height; Set Screw Mount; Ball Bearing; 204MM M |
|-------------------------------|---|
| UNSPSC | 31171511 |
| Harmonized Tariff Code | 8483.20.40.40 |
| Noun | Bearing |
| Keyword String | Pillow Block |
| Manufacturer Item Number | UCP215C4HR23 |
| Weight / LBS | 17.6 |
| D | 3.063 Inch 77.8 Millimeter |
| Actual Bolt Center to Center | 0 Inch 0Millimeter |
| Nominal Bolt Center to Center | 8.5 Inch 215.5 Millimeter |
| Bolt Spacing Maximum | 8.976 Inch 228Millimeter |
| d | 2.953 Inch 75 Millimeter |
| В | 3.252 Inch 82.6 Millimeter |
| Bolt Spacing Minimum | 8.031 Inch 204Millimeter |