

IKO GBR 223020 UU needle roller bearings

Can't find what you're looking for IKO GBR 223020 UU needle roller bearings ? Our TIMKEN Manufacturer Name expert Representatives be in contact with you shortly! 0.0 Inventory

Inventory	0.0
Manufacturer Name	TIMKEN
Minimum Buy Quantity	N/A
Weight	17.0 lb
EAN	0053893778372
Product Group	M06288
Number of Mounting Holes	4
Mounting Method	Concentric Collar
Housing Style	4 Bolt Round Flange Block
Rolling Element	Tapered Roller Bearing
Housing Material	Cast Iron
Expansion / Non-expansion	Non-expansion
Mounting Bolts	1/2 Inch
Relubricatable	Yes
Seals	Double Lip Radial
Housing Configuration	1 Piece Solid
Pilot Configuration	With Pilot
Inch – Metric	Inch
Long Description	4 Bolt Round Flange Block; 2-1/2" Bore; 6-1/2" Bolt Circle; 4.6" Bolt Spacing; 1 Piec

Other Features	Double Row Wide Inner Race With Set Screw
UNSPSC	31171501
Harmonized Tariff Code	8483.20.40.80
Noun	Bearing
Keyword String	Flanged
Manufacturer Item Number	E-PF-TRB-2 1/2
Weight / LBS	17
D	4 Inch 101.6 Millimeter
d	2.5 Inch 63.5 Millimeter
Cartridge Pilot Depth	2.125 Inch 53.975 Millimeter
Nominal Bolt Circle Diameter Round	6.5 Inch 165 Millimeter
Bolt Spacing	4.6 Inch 117 Millimeter
Cartridge Pilot Diameter	5.5 Inch 139.7 Millimeter
Shaft Size	2.5 in
Shaft Size Type	Imperial
UPC Code	053893778372
Nose Diameter	5.37 in
Nose Bore Diameter	4.1 in
Dimension B	4 in
Dimension H	7-5/8 in
Dimension A	3-5/16 in
Dimension N2	4.600 in
Dimension J	6-1/2 in
Dimension A3	1-5/16 in
Bolt Diameter	1/2 in
Dimension E	1-13/16 in
Dimension A1	5/8 in

Dimension D 1	5-1/2 in
Dimension d1	4-1/16 in
Dimension A2	1-3/16 in
e	0.40
X (if $F_a/F_r \leq e$)	0.87
Y (if $F_a/F_r \leq e$)	2.17
X (if $F_a/F_r > e$)	0.7
Y (if $F_a/F_r > e$)	2.63
K Factor	1.51
C90 Dynamic Load Rating ²	11600 lb
C0 Static Load Rating	54000 lb
Fa-max Maximum Permissible Thrust Load ³	3454 lb
Fr-max Maximum Allowable Slip Fit Radial Load ⁴	9500 lb
Max. Speed ⁵	2420 rpm
Note	Note: All units have a 1/8 pipe thread grease fitting The Maximum Permissible Thrust Load applies to